



PRODUCT DATA SHEET	
YOLO Colorhouse Inside – Transitional Primer	110519

- **ZERO VOC**
- **LOW ODOR**
- **EXCELLENT HIDE**
- **ALLOWS TRANSITION FROM OIL TO WATER-BASED PAINT**

YOLO Colorhouse® began with the elemental – what to put into our paint and what to leave out. With high volume solids and Green Seal™ certification, YOLO Colorhouse Transitional Primer performs like a premium conventional transitional primer, yet it has low odor, no harmful chemicals, and no added solvents. YOLO Colorhouse Transitional Primer should be used when transitioning a surface from an oil-based paint to a water-based latex or acrylic paint.

**USAGE** A zero VOC, low odor transitional primer for interior or exterior use.

**AVAILABILITY** Quarts and 1 Gallon containers.

**COVERAGE** 300 sq. feet per gallon.

**DRY TIME** At 77°F and 50% relative humidity: dry time to touch is 1 hour. Allow 8 hours to recoat. For best results, allow 24 hours before recoating. Increased bonding and adhesion will continue over 8 days of curing.

**SURFACE PREPARATION** Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, wax, and mildew. High gloss surfaces must be dulled using a wet scouring or sanding pad. Surface must be completely dry before application. Remove peeling paint or loose material on surface\*. Do not apply to unprimed metal surfaces.

\*Warning!: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**APPLICATION** Mix transitional primer thoroughly before use. Keep lid on can of unused portion to prevent skinning. Use YOLO Colorhouse transitional primer before applying YOLO Colorhouse paint over oil-based paint. Apply with a high quality brush for trim and to cut-in edges. For wall surfaces, use a roller with 3/8" to 3/4" nap roller cover. For airless sprayer – no thinning is recommended, 2000-2500 PSI, tip – .015"-.021". For conventional sprayer and HVLP, reduce up to 1 pint per gallon with clean water.

**CLEAN UP** Remove excess primer from equipment before washing with water.

**THINNING** Thinning is not recommended.

**DISPOSAL** Check [www.earth911.org](http://www.earth911.org) for recycling and disposal information in your area. Do not pour unused contents down drain. Pour into absorbent material, let dry and dispose with trash – OR take to hazardous waste collection program.

#### PHYSICAL PROPERTIES

**Viscosity range:** 100 ± 2 KU

**Solids Volume:** 38 ± 2

**Solids Weight:** 55 ± 2

**Odor:** No toxic or offensive odor during painting, no odor once dried

**Toxic Properties:** Non-toxic

**Weight:** 11.4 lbs. per gallon

**Theoretical VOC:** Zero

**Gloss:** Flat (Transitional Primer)

**LIMITATIONS** Do not apply when surface or air temperatures are expected to drop below 50°F (10°C) or rise above 95°F (35°C) during application and drying. Keep from freezing. NOT RECOMMENDED FOR UNPAINTED METAL OR BLEEDING WOODS.

Disclaimer: All technical advice, recommendations, and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice, or services are not to be taken as a license to operate under or suggest infringement of any patent.

[www.yolocolorhouse.com](http://www.yolocolorhouse.com)

© 2007 YOLO Colorhouse® is a registered trademark of YOLO Colorhouse LLC.

1001 SE Water Ave  
Suite 140  
Portland, OR 97214  
503-493-8275

