



PRODUCT DATA SHEET

YOLO Colorhouse Inside – Semi-Gloss Cabinet/Trim

111615

- **ZERO VOC**
- **LOW ODOR**
- **DURABLE AND WASHABLE**
- **FAST DRYING**
- **WATER CLEAN-UP**
- **SELECT DESIGNER PALETTE**

YOLO Colorhouse® began with the elemental – what to put into our paint and what to leave out. With 40% volume solids and Green Seal™ certification, YOLO Colorhouse performs like a premium conventional paint, yet it has low odor, no harmful chemicals, and no added solvents. YOLO Colorhouse is a premium, 100% acrylic paint with excellent hide and durability.

USAGE A zero VOC, low odor, semi-gloss finish for cabinets and trim.

AVAILABILITY Quart and Gallon containers. White and Midtone bases only.

COVERAGE 400 sq. feet per gallon.

DRY TIME At 77°F and 50% humidity: dry time to touch is 40 min. and dry time to re-coat is 2 hours. Allow 48 hours to cure before placing objects on painted surfaces or closing doors.

SURFACE PREPARATION Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, wax, and mildew. Remove peeling paint or loose material on surface*. Feather by sanding or fill with spackle and then prime. Glossy surfaces must be dulled or primed for best results. Use YOLO Colorhouse Primer for new wood or when going from a dark to light color. Use YOLO Colorhouse Transitional Primer when transitioning from an oil-base paint to YOLO cabinet and trim. If previously painted with latex, no priming is necessary.

*Warning! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION Mix paint thoroughly before use. Keep lid on can of unused portion to prevent skinning. Apply with a high-quality nylon brush. Do not over brush. For airless sprayer – no thinning is recommended, 2000-2500 PSI, tip – .015" – .021". For conventional sprayer – thin as needed with clean water.

CLEAN UP Remove excess paint from equipment before washing with water.

THINNING Thinning is not recommended.

DISPOSAL Check www.earth911.org for recycling and disposal information in your area. Do not pour unused contents down drain. Pour into absorbent material, let dry and dispose with trash – OR take to hazardous waste collection program.

PHYSICAL PROPERTIES

Viscosity range: 97 ± 2 KU

Solids Volume: 40 ± 2

Solids Weight: 52 ± 2

Odor: No toxic or offensive odor during painting, no odor once dried

Toxic Properties: Non-toxic

Weight: 9.10 lbs. per gallon

Theoretical VOC: Zero

Gloss: 60° – 40.6 (Semi-gloss)

LIMITATIONS Do not apply when surface or air temperatures are expected to drop below 50°F (10°C) or rise above 95°F (35°C) during application and drying. Keep from freezing. Available in White and Midtone bases only.

Disclaimer: All technical advice, recommendations, and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice, or services are not to be taken as a license to operate under or suggest infringement of any patent.

www.yolocolorhouse.com

© 2007 YOLO Colorhouse® is a registered trademark of YOLO Colorhouse LLC.

116 SE Yamhill Street
Portland, OR 97214
503-493-8275

