



## PRODUCT DATA SHEET

YOLO Colorhouse Outside – Primer

150416

- **ZERO VOC**
- **LOW ODOR**
- **EXCELLENT HIDE AND DURABILITY**
- **SUPERIOR ADHESION**

YOLO Colorhouse® began with the elemental – what to put into our paint and what to leave out. With  $39 \pm 2$  percent volume solids and Green Seal™ certification, YOLO Colorhouse Outside Primer performs like a premium conventional exterior primer, yet it has low odor, no harmful chemicals, and no added solvents. YOLO Colorhouse Outside Primer has excellent hide, durability, and adhesion. Use YOLO Colorhouse primer for a complete zero VOC system.

**USAGE** A zero VOC, 100% acrylic primer for exterior use.

**AVAILABILITY** 1 Gallon and Five gallon containers.

**COVERAGE** 300-400 sq. feet per gallon.

**DRY TIME** At 77°F and 50% humidity: dry time to touch is 30 min. and dry time to re-coat is 1-2 hours.

**SURFACE PREPARATION** Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, excessive chalking, and mildew. Remove peeling paint or loose material on surface\*. Use YOLO Colorhouse Outside Primer for non-bleeding, bare, or new wood, cured masonry and plaster, spackled areas, and when going from a dark to light color. New plaster or masonry must be allowed to cure 30-60 days before priming. Not recommended for new cedar, redwood or unpainted metal.

\*Warning!: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**APPLICATION** Mix primer thoroughly before use. Keep lid on can of unused portion to prevent skinning. Loose, sandy masonry should be hosed down thoroughly to remove particles, allowed to dry, and then primed with YOLO Colorhouse Outside Primer. Two coats provide maximum sealing. Apply with a high quality brush, roller, or sprayer. For airless sprayer – no thinning is recommended, 2000-2500 PSI, tip – .015"-.021". For conventional and HVLP, reduce up to 1 pint per gallon with clean water.

**CLEAN UP** Remove excess primer from equipment before washing with water.

**THINNING** Thinning is not recommended.

**DISPOSAL** Check [www.earth911.org](http://www.earth911.org) for recycling and disposal information in your area. Do not pour unused contents down drain. Pour into absorbent material, let dry and dispose with trash – OR take to hazardous waste collection program.

### PHYSICAL PROPERTIES

**Viscosity range:**  $100 \pm 2$  KU

**Solids Volume:**  $39 \pm 2$

**Solids Weight:**  $55 \pm 2$

**Odor:** No toxic or offensive odor during painting, no odor once dried

**Toxic Properties:** Non-toxic

**Weight:** 11.4 lbs. per gallon

**Theoretical VOC:** Zero

**Gloss:** Flat (Exterior Primer)

**LIMITATIONS** Do not apply when surface or air temperatures are expected to drop below 50°F (10°C) or rise above 95°F (35°C) during application and drying. Keep from freezing. NOT RECOMMENDED FOR UNPAINTED METAL OR BLEEDING WOODS.

Disclaimer: All technical advice, recommendations, and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice, or services are not to be taken as a license to operate under or suggest infringement of any patent.

[www.yolocolorhouse.com](http://www.yolocolorhouse.com)

© 2007 YOLO Colorhouse® is a registered trademark of YOLO Colorhouse LLC.

116 SE Yamhill Street  
Portland, OR 97214  
503-493-8275

